

Facing Temperature Measurement Challenges?

Meet The OPTITEMP TT 12 C



- ? Need cost-effective temperature monitoring for RTD or thermocouple (TC) sensors?
- ? Looking for a compact, reliable solution for HVAC systems or food and beverage applications?
- ? Struggling with harsh conditions like shocks, vibrations, or high humidity?

💡 If these challenges sound familiar, the [OPTITEMP TT 12 C](#) is your answer:

✓ This universal, programmable 2-wire head-mounted temperature transmitter offers reliable performance in all basic applications. With its ultra-compact design (just 10.5 mm high), it easily fits into all DIN B connection heads. Its robust construction withstands shocks up to 10 g and harsh environmental conditions, making it perfect for demanding applications.

👋 Say goodbye to complex setups! Configure the OPTITEMP TT 12 C wirelessly via NFC using your smartphone or tablet and the OPTICHECK Temperature Mobile app, no cables or power supply needed. With a long-term stability of $\pm 0.05^{\circ}\text{C}/\text{year}$, it ensures minimal drift and reduces the need for frequent recalibration.



Krohne
**OPTITEMP TT
12 C**
Head-mounted temperature
transmitter with RTD or TC input

[Learn More](#)

[More Related Products](#)

[Make an Inquiry](#)



Semac Automation S.A.

www.semac.gr

Industrial Area of Sindos, Block 39B, Box 1262, Sindos 57022, GR
Ethnikis Antistaseos 125 Str, Drapetsona 18648, GR

Tel. Thessaloniki: (+30) 231 056-9031

Tel. Athens: (+30) 210 462-2625

This email was sent to {{contact.EMAIL}}.

[View in browser](#) | [Unsubscribe](#)



